


Product Information

DE-F423



Material description:	thermal transfer printable polyester film, satin-silver, matte; complies with VW specification TL52038 and TL1010; UL MH48716 ^{*)}															
Applications:	automotive and electronics industry															
Label stock thickness:	50 µm ± 10%															
Adhesive:	AS4: acrylic adhesive; solvent-based															
Adhesive thickness:	27 µm ± 10%															
Adhesion:	very strong adhesive															
Adhesion power:	<table><tr><td>stainless steel:</td><td>20,6 N/25 mm</td><td>FTM1</td></tr><tr><td>glass:</td><td>21,9 N/25 mm</td><td>FTM1</td></tr><tr><td>polypropylene:</td><td>17,5 N/25 mm</td><td>FTM1</td></tr><tr><td>automotive paint:</td><td>19,5 N/25 mm</td><td>FTM1</td></tr><tr><td>PBT:</td><td>18,0 N/25 mm</td><td>FTM1</td></tr></table>	stainless steel:	20,6 N/25 mm	FTM1	glass:	21,9 N/25 mm	FTM1	polypropylene:	17,5 N/25 mm	FTM1	automotive paint:	19,5 N/25 mm	FTM1	PBT:	18,0 N/25 mm	FTM1
stainless steel:	20,6 N/25 mm	FTM1														
glass:	21,9 N/25 mm	FTM1														
polypropylene:	17,5 N/25 mm	FTM1														
automotive paint:	19,5 N/25 mm	FTM1														
PBT:	18,0 N/25 mm	FTM1														
Liner:	glassine															
Liner thickness:	56 µm ± 10%															
Temperature range:	- 40 °C to + 150 °C															
Application temperature:	> + 10 °C															
Print method:	thermal transfer															
Ribbon recommendation:	DE-R99, DE-R25 ^{*)} (unprinted material surface)															
Shelf life:	2 years at max. 22 °C and 50 % relative humidity															

^{*)} UL recognised component 

Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.5

create date 2016-08-02