

## Product Information

DE-F567



<b>Material description:</b>	Polyimide film, coated on one side, white, glossy, without adhesive, high level of resistance to tear, high and low temperatures, as well as chemicals
<b>Applications:</b>	Identification of items which are exposed to very high temperatures; good printability via thermal transfer print
<b>Label stock thickness:</b>	100 µm
<b>Top coat thickness:</b>	17 µm
<b>Total material thickness:</b>	117 µm
<b>Temperature range:</b>	max. + 300 ° C to + 400 ° C short term: max. up to + 600 ° C
<b>Print method:</b>	Thermal transfer
<b>Ribbon recommendation:</b>	DE-R25, DE-R89
<b>Shelf life:</b>	1 year at 27 ° C and 60 % relative humidity

### Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

**Dynamic Systems GmbH** • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96  
e-Mail: [info@dynamic-systems.de](mailto:info@dynamic-systems.de) • Internet: [www.dynamic-systems.de](http://www.dynamic-systems.de) • HRB Nr. 116251 Reg. Gericht München • V1.0