

Product Information

DE-F 810



Material description:	Cast vinyl film, white, glossy, excellent adhesion on LSE surfaces such as rough and textured surfaces, hammer paint, as well as plastic materials, e. g. polypropylene or polyethylene
Applications:	due to high durability recommended for indoor and outdoor use, thermal transfer printable
Label stock thickness:	50 µm
Adhesive:	AS4: solvent-based acrylic adhesive
Adhesion:	very strong adhesive
Adhesion power:	Glass: 22N/25 mm FTM1 Shear strength on stainless steel: 100 h+ FTM8 with weight of 1 kg
Liner:	glassine paper
Liner thickness:	56 µm
Temperature range:	- 40 °C to + 90 °C
Application temperature:	> + 10 °C
Print method:	Thermal transfer, flexo printing, silk screen printing
Ribbon recommendation:	DE-R89, DE-R93
Durability:	10 years (outdoor use)
Shelf life:	2 years at max. + 21 ° C and 50 % r. h.

Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.1